

C2700

LEADED BRASS

DESCRIPTION

C2700, Engraving brass, are 60/40 alpha-beta brasses with different levels of lead added to give free machining properties. They are widely used for engraved plates and plaques, builders hardware, gears. They should not be used for acid etched work, for which the single phase alpha brasses should be used.

CHEMICAL COMPOSITION

Elements	Min (%)	Max (%)
Cu	63.00	67.00
Pb	-	0.05
Fe	-	0.05
Zn	Remainder	

MECHANICAL PROPERTIES ACCORDING TO JIS C3712 (AS PER TEMPER BD)

Range (Inch)	From	To	UTS Min (Mpa)	PS Min	Elongation Min (%)	Hardness Min	Hardness Max
Round (Dia)	1.5	75.00	355.00	-	10.00	-	-
	6.00	50.00	355.00	-	20.00	-	-
Hex (A/F)	3.00	70.00	355.00	-	10.00	-	-
	6.00	50.00	355.00	-	20.00	-	-
Square (A/F)	3.00	60.00	355.00	-	10.00	-	-
	6.00	50.00	355.00	-	20.00	-	-
Rectangle (Thickness)	3.00	50.00	355.00	-	10.00	-	-
	6.00	50.00	355.00	-	20.00	-	-



PHYSICAL PROPERTIES

Melting Point - Liquidus°F	1710
Melting Point - Solidus°F	1660
Densitylb/cu in. at 68°F	0.306
Specific Gravity	8.47
Electrical Conductivity% IACS at 68°F	27
Thermal ConductivityBtu/ sq ft/ ft hr/ °F at 68°F	67
Coefficient of Thermal Expansion 68-57210 ⁻⁶ per °F (68 – 572°F)	11.3
Specific Heat CapacityBtu/ lb /°F at 68°F	0.09
Modulus of Elasticity in Tensionksi	15000
Modulus of Rigidityksi	5600

FABRICATION PROPERTIES

Technique	Suitability
Soldering	Excellent
Brazing	Excellent
Oxyacetylene Welding	Good
Gas Shielded Arc Welding	Fair
Coated Metal Arc Welding	Not Recommended
Spot Weld	Good
Seam Weld	Not Recommended
Butt Weld	Good
Capacity for Being Cold Worked	Excellent
Capacity for Being Hot Formed	Poor
Machinability Rating	30

TYPICAL USES

- Plumbing

